## NSN 4140-00-289-8862

Vaneaxial Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-00-289-8862 Stage Quantity: **Speed Adjustments:** Single speed Length: 29.625 inches Flow Direction: Outward **Ambient Tempurature At Full Rated Power:** 50.0 degrees celsius **Operating Speed At Rated Capacity In Rpm:** 1750.0 **Electrical Connection Type:** Terminal block Static Pressure At Specificationified Air Flow Rate: 0.0 inches of water **Drive Type:** Direct **Prime Mover Type:** Electric motor

Inclosure Type:
Fully enclosed
Mounting Facility Type And Quantity:
1 flange
Rotation Direction For Which Designed:
Clockwise
Features Provided:
Safety impeller guard
Voltage In Volts And Current Type:
440.0 ac
Prime Mover Power Rating:
3.000 horsepower
Housing Inside Diameter:
21.125 inches
Prime Mover Drive Shaft Bearing Type:
Ball
Phase:
Three
Frequency In Hertz:
60.0
Material:
Aluminum alloy housing

## NSN 4140-00-289-8862

Vaneaxial Fan - Page 2 of 2



M	late	rial	Sp	ecif	icat	ion:
			~	••••		. •

Qq-a-250/11 federal specification single material response housing

**Style Designator:** 

Fixed

## **Test Data Document:**

81349-milf18953 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A087a0