NSN 4140-00-289-8885

Vaneaxial Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-00-289-8885 **Speed Adjustments:** Single speed Length: 26.000 inches Flow Direction: Outward **Environmental Protection:** Splash proof **Ambient Tempurature At Full Rated Power:** 65.0 degrees celsius **Operating Speed At Rated Capacity In Rpm:** 3450.0 **Electrical Connection Type:** Terminal block Static Pressure At Specificationified Air Flow Rate: 0.0 inches of water **Drive Type:** Direct **Prime Mover Type:** Electric motor **Inclosure Type:** Fully enclosed **Mounting Facility Type And Quantity:** 1 flange **Rotation Direction For Which Designed:** Clockwise **Features Provided:** Safety impeller guard Air Flow Rate: 2000.0 cubic feet per minute **Voltage In Volts And Current Type:** 440.0 ac **Prime Mover Power Rating:** 1.500 horsepower **Housing Inside Diameter:** 15.500 inches **Prime Mover Drive Shaft Bearing Type:** Ball Phase: Three Frequency In Hertz:

60.0

NSN 4140-00-289-8885

Vaneaxial Fan - Page 2 of 2

Mil-std (military Standard):

Mil-f-18953 spec.



| Material: |
|--|
| Aluminum alloy housing |
| Material Specification: |
| Qq-a-250/11 federal specification single material response housing |
| Style Designator: |
| Fixed |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A087a0 |