

View Online at <https://aerobasegroup.com/nsn/4140-00-289-8886>

Speed Adjustments:

Single speed

Length:

26.000 inches

Flow Direction:

Outward

Environmental Protection:

Splash proof

Ambient Temperature At Full Rated Power:

65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3450.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Safety impeller guard

Air Flow Rate:

2000.0 cubic feet per minute

Voltage In Volts And Current Type:

440.0 ac

Prime Mover Power Rating:

1.500 horsepower

Housing Inside Diameter:

15.500 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Special Features:

Non-magnetic

Frequency In Hertz:

60.0

Material:

Aluminum alloy housing

Material Specification:

Qq-a-250/11 federal specification single material response housing

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0

Mil-std (military Standard):

Mil-f-18953 spec.