

View Online at <https://aerobasegroup.com/nsn/4140-00-289-8886>

**Speed Adjustments:**

Single speed

**Length:**

26.000 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Splash proof

**Ambient Temperature At Full Rated Power:**

65.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3450.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Safety impeller guard

**Air Flow Rate:**

2000.0 cubic feet per minute

**Voltage In Volts And Current Type:**

440.0 ac

**Prime Mover Power Rating:**

1.500 horsepower

**Housing Inside Diameter:**

15.500 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Special Features:**

Non-magnetic

**Frequency In Hertz:**

60.0

**Material:**

Aluminum alloy housing

**Material Specification:**

Qq-a-250/11 federal specification single material response housing

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0

**Mil-std (military Standard):**

Mil-f-18953 spec.