

View Online at <https://aerobasegroup.com/nsn/4140-00-311-6329>

Speed Adjustments:

Single speed

Width:

4.680 inches

Diameter:

4.000 inches

Length:

2.130 inches

Flow Direction:

Outward

Environmental Protection:

Fungus resistant and humidity proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

85.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

7100.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 4 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

170.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.087 horsepower

Housing Inside Diameter:

4.065 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Height:

4.680 inches

Material:

Aluminum

Quantity:

1

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0

Mil-std (military Standard):

Mil-c-5541 spec.