Circulating Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-00-330-3570

| Speed Adjustments: |
|--|
| Single speed |
| Diameter: |
| 7.000 inches |
| Length: |
| 5.500 inches |
| Flow Direction: |
| Inward |
| Ambient Tempurature At Full Rated Power: |
| 40.0 degrees celsius |
| Operating Speed At Rated Capacity In Rpm: |
| 3400.0 |
| Electrical Connection Type: |
| Wire lead |
| Static Pressure At Specificationified Air Flow Rate: |
| 0.0 inches of water |
| Drive Type: |
| Direct |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Partially enclosed |
| Mounting Facility Type And Quantity: |
| 1 bracket and 3 lug |
| Rotation Direction For Which Designed: |
| Counterclockwise |
| Air Flow Rate: |
| 520.000 cubic feet per minute |
| Voltage In Volts And Current Type: |
| 115.0 ac |
| Prime Mover Power Rating: |
| 0.077 horsepower |
| Housing Inside Diameter: |
| 7.190 inches |
| Prime Mover Drive Shaft Bearing Type: |
| Ball |
| Phase: |
| Single |
| Frequency In Hertz: |
| 60.0 |
| Material: |
| |
| Aluminum alloy |

NSN 4140-00-330-3570

Circulating Fan - Page 2 of 2

Quantity: Surface Treatment:

Anodize

1

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A087a0

