

View Online at <https://aerobasegroup.com/nsn/4140-00-335-2863>

Speed Adjustments:

Three speed

Length:

Between 1.404 inches and 1.410 inches

Flow Direction:

Outward

Environmental Protection:

Explosion proof and fungus resistant and humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

0.0 degrees celsius and 71.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

4800.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

165.0 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

42.0 watts

Housing Inside Diameter:

4.500 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Material:

Aluminum

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0