

View Online at <https://aerobasegroup.com/nsn/4140-00-338-8770>

**Stage Quantity:**

1

**Environmental Protection:**

Moisture resistant and shock proof and spray tight and vibration proof

**Ambient Temperature At Full Rated Power:**

-0.0 degrees celsius and -70.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3350.0

**Electrical Connection Type:**

Wire lead

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

6 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Outlet Location:**

Bottom

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Vertical down

**Phase:**

Three

**Special Features:**

Life time ball bearings, wire leads 36 in. L, 4.4 amps running, 5.5 amps starting or locked rotor, 484 maximum watts, insulation rated at 155 degrees c

**Frequency In Hertz:**

400.0

**Material:**

Aluminum alloy blade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0