

View Online at <https://aerobasegroup.com/nsn/4140-00-356-0517>

Speed Adjustments:

Single speed

Diameter:

7.500 inches

Length:

9.500 inches

Flow Direction:

Inward

Environmental Protection:

Explosion proof

Ambient Temperature At Full Rated Power:

-65.0 degrees fahrenheit and 160.0 degrees fahrenheit

Operating Speed At Rated Capacity In Rpm:

11500.0

End Application:

Ch-53g, hh-53c blower heating system

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

15.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 12 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

1300.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac or 200.0 ac

Prime Mover Power Rating:

5.000 horsepower

Housing Inside Diameter:

9.500 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Material:

Magnesium

Quantity:

1

Unpackaged Unit Weight:

14.000 pounds

Reference Data And Literature (non-core):

F09603-81-g-1808

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A087a0