

View Online at <https://aerobasegroup.com/nsn/4140-00-360-2397>

Stage Quantity:

1

Speed Adjustments:

Single speed

Diameter:

Between 1.062 inches and 1.125 inches

Length:

Between 1.375 inches and 1.438 inches

Flow Direction:

Inward

Ambient Temperature At Full Rated Power:

25.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

16200.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

1.5 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 clamp ring

Rotation Direction For Which Designed:

Counterclockwise

Features Provided:

Radio interference shielding

Air Flow Rate:

42.650 cubic feet per minute

Housing Inside Diameter:

Between 2.166 inches and 2.186 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Special Features:

Voltage in volts 26.0, input current 1.7a maximum starting, 1.41 a maximum running, input power 40.4 watts max, 1 6 mfd 150 v capacitor supplied in other package

Frequency In Hertz:

380.0 and 420.0

Material:

Aluminum

Quantity:

1

Surface Treatment:

Anodize housing outside and enamel housing outside

Surface Treatment Specification:

Mil-e-5557, type 4 military specification single treatment response blade

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0

Mil-std (military Standard):

Mil-e-5557 spec.