

View Online at <https://aerobasegroup.com/nsn/4140-00-395-0027>

**Speed Adjustments:**

Single speed

**Length:**

8.500 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Fungus resistant and shock proof and spray proof

**Ambient Temperature At Full Rated Power:**

80.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3250.0

**Electrical Connection Type:**

Connector receptacle

**Static Pressure At Specificationified Air Flow Rate:**

0.1 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange and 12 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

950.000 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.333 horsepower

**Housing Inside Diameter:**

9.875 inches

**Phase:**

Single

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Aluminum

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-a-8625 spec.