## NSN 4140-00-400-7999

Tubeaxial Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-00-400-7999

Speed Adjustments:
Single speed
Width:
4.688 inches
Length:
1.500 inches
Flow Direction:
Outward
Environmental Protection:
Dustproof and moisture resistant and salt spray resistant and vibration proof
Operating Speed At Rated Capacity In Rpm:
2600.0
Electrical Connection Type:
Terminal block
Static Pressure At Specificationified Air Flow Rate:
0.0 inches of water
Drive Type:
Direct
Prime Mover Type:
Electric motor
Inclosure Type:
<b>7</b> 1
Fully enclosed
Fully enclosed
Fully enclosed  Mounting Facility Type And Quantity:
Fully enclosed  Mounting Facility Type And Quantity:  2 flange and 4 unthreaded hole
Fully enclosed  Mounting Facility Type And Quantity:  2 flange and 4 unthreaded hole  Rotation Direction For Which Designed:
Fully enclosed  Mounting Facility Type And Quantity: 2 flange and 4 unthreaded hole  Rotation Direction For Which Designed: Counterclockwise
Fully enclosed  Mounting Facility Type And Quantity:  2 flange and 4 unthreaded hole  Rotation Direction For Which Designed:  Counterclockwise  Air Flow Rate:
Fully enclosed  Mounting Facility Type And Quantity:  2 flange and 4 unthreaded hole  Rotation Direction For Which Designed:  Counterclockwise  Air Flow Rate:  92.0 cubic feet per minute
Fully enclosed  Mounting Facility Type And Quantity:  2 flange and 4 unthreaded hole  Rotation Direction For Which Designed:  Counterclockwise  Air Flow Rate:  92.0 cubic feet per minute  Voltage In Volts And Current Type:
Fully enclosed  Mounting Facility Type And Quantity:  2 flange and 4 unthreaded hole  Rotation Direction For Which Designed:  Counterclockwise  Air Flow Rate:  92.0 cubic feet per minute  Voltage In Volts And Current Type:  115.0 ac  Prime Mover Power Rating:
Fully enclosed  Mounting Facility Type And Quantity:  2 flange and 4 unthreaded hole  Rotation Direction For Which Designed:  Counterclockwise  Air Flow Rate:  92.0 cubic feet per minute  Voltage In Volts And Current Type:  115.0 ac  Prime Mover Power Rating:  0.003 horsepower
Fully enclosed  Mounting Facility Type And Quantity:  2 flange and 4 unthreaded hole  Rotation Direction For Which Designed:  Counterclockwise  Air Flow Rate:  92.0 cubic feet per minute  Voltage In Volts And Current Type:  115.0 ac  Prime Mover Power Rating:
Fully enclosed  Mounting Facility Type And Quantity: 2 flange and 4 unthreaded hole  Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 92.0 cubic feet per minute  Voltage In Volts And Current Type: 115.0 ac  Prime Mover Power Rating: 0.003 horsepower  Housing Inside Diameter: 4.517 inches
Fully enclosed  Mounting Facility Type And Quantity:  2 flange and 4 unthreaded hole  Rotation Direction For Which Designed:  Counterclockwise  Air Flow Rate:  92.0 cubic feet per minute  Voltage In Volts And Current Type:  115.0 ac  Prime Mover Power Rating:  0.003 horsepower  Housing Inside Diameter:
Fully enclosed  Mounting Facility Type And Quantity: 2 flange and 4 unthreaded hole  Rotation Direction For Which Designed: Counterclockwise  Air Flow Rate: 92.0 cubic feet per minute  Voltage In Volts And Current Type: 115.0 ac  Prime Mover Power Rating: 0.003 horsepower  Housing Inside Diameter: 4.517 inches  Prime Mover Drive Shaft Bearing Type:
Fully enclosed  Mounting Facility Type And Quantity:  2 flange and 4 unthreaded hole  Rotation Direction For Which Designed:  Counterclockwise  Air Flow Rate:  92.0 cubic feet per minute  Voltage In Volts And Current Type:  115.0 ac  Prime Mover Power Rating:  0.003 horsepower  Housing Inside Diameter:  4.517 inches  Prime Mover Drive Shaft Bearing Type:  Ball  Phase:
Fully enclosed  Mounting Facility Type And Quantity:  2 flange and 4 unthreaded hole  Rotation Direction For Which Designed:  Counterclockwise  Air Flow Rate:  92.0 cubic feet per minute  Voltage In Volts And Current Type:  115.0 ac  Prime Mover Power Rating:  0.003 horsepower  Housing Inside Diameter:  4.517 inches  Prime Mover Drive Shaft Bearing Type:  Ball  Phase:  Single
Fully enclosed  Mounting Facility Type And Quantity:  2 flange and 4 unthreaded hole  Rotation Direction For Which Designed:  Counterclockwise  Air Flow Rate:  92.0 cubic feet per minute  Voltage In Volts And Current Type:  115.0 ac  Prime Mover Power Rating:  0.003 horsepower  Housing Inside Diameter:  4.517 inches  Prime Mover Drive Shaft Bearing Type:  Ball  Phase:

50.0 and 60.0 and 400.0

## NSN 4140-00-400-7999

Tubeaxial Fan - Page 2 of 2



Height:
4.688 inches
Material:
Zinc housing
Surface Treatment:
Enamel semigloss housing
Style Designator:
Fixed
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A087a0