

View Online at <https://aerobasegroup.com/nsn/4140-00-403-7367>

Stage Quantity:

1

Speed Adjustments:

Single speed

Diameter:

3.000 inches

Length:

2.310 inches

Flow Direction:

Inward

Environmental Protection:

Moisture resistant

Ambient Temperature At Full Rated Power:

-28.0 degrees celsius and 65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

22500.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Nonsparking

Air Flow Rate:

157.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.181 horsepower

Housing Inside Diameter:

2.812 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

60.0

Material:

Aluminum housing

Quantity:

1

Surface Treatment:

Enamel blade

Surface Treatment Specification:

II-e-5557, type 2 military specification 10th treatment response blade

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0

Mil-std (military Standard):

spec.