

View Online at <https://aerobasegroup.com/nsn/4140-00-403-7367>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Diameter:**

3.000 inches

**Length:**

2.310 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Moisture resistant

**Ambient Temperature At Full Rated Power:**

-28.0 degrees celsius and 65.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

22500.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 rim

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Nonsparking

**Air Flow Rate:**

157.000 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.181 horsepower

**Housing Inside Diameter:**

2.812 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

60.0

**Material:**

Aluminum housing

**Quantity:**

1

**Surface Treatment:**

Enamel blade

**Surface Treatment Specification:**

II-e-5557, type 2 military specification 10th treatment response blade

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0

**Mil-std (military Standard):**

spec.