

View Online at <https://aerobasegroup.com/nsn/4140-00-405-8044>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Length:**

Between 1.375 inches and 1.437 inches

**Flow Direction:**

Inward

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 125.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

20000.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

2.8 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 clamp ring

**Rotation Direction For Which Designed:**

Counterclockwise

**Features Provided:**

Radio interference shielding

**Air Flow Rate:**

Between 54.150 cubic feet per minute and 56.050 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Housing Inside Diameter:**

1.907 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Special Features:**

Voltage in volts and current type, square wave 126.0

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Quantity:**

1

**Surface Treatment:**

Anodize housing outside and enamel housing outside

**Surface Treatment Specification:**

Mil-e-5557, type 4 military specification single treatment response blade

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0

**Mil-std (military Standard):**

Mil-e-5557 spec.