

View Online at <https://aerobasegroup.com/nsn/4140-00-405-8044>

Stage Quantity:

1

Speed Adjustments:

Single speed

Length:

Between 1.375 inches and 1.437 inches

Flow Direction:

Inward

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 125.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

20000.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

2.8 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 clamp ring

Rotation Direction For Which Designed:

Counterclockwise

Features Provided:

Radio interference shielding

Air Flow Rate:

Between 54.150 cubic feet per minute and 56.050 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Housing Inside Diameter:

1.907 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Special Features:

Voltage in volts and current type, square wave 126.0

Frequency In Hertz:

400.0

Material:

Aluminum

Quantity:

1

Surface Treatment:

Anodize housing outside and enamel housing outside

Surface Treatment Specification:

Mil-e-5557, type 4 military specification single treatment response blade

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0

Mil-std (military Standard):

Mil-e-5557 spec.