## NSN 4140-00-412-2076

Vaneaxial Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-00-412-2076 **Stage Quantity: Speed Adjustments:** Single speed Length: 2.125 inches Flow Direction: Inward **Operating Speed At Rated Capacity In Rpm:** 13000.0 and 20000.0 **Electrical Connection Type:** Wire lead Static Pressure At Specificationified Air Flow Rate: 0.0 inches of water **Drive Type:** Direct **Prime Mover Type:** Electric motor **Inclosure Type:** Fully enclosed **Mounting Facility Type And Quantity:** 1 flange and 4 unthreaded hole **Rotation Direction For Which Designed:** Counterclockwise Air Flow Rate: 31.0 cubic feet per minute **Voltage In Volts And Current Type:** 208.0 ac **Prime Mover Power Rating:** 0.020 horsepower **Housing Inside Diameter:** 2.000 inches **Prime Mover Drive Shaft Bearing Type:** Ball Phase: Three **Special Features:** W/2.12 in. Sq flange w/hole ea corner at intake end of venturi tube Frequency In Hertz: 400.0

Material:

Zinc alloy housing

## NSN 4140-00-412-2076

Vaneaxial Fan - Page 2 of 2



Surrace	reatment

Enamel housing

Style Designator:

Fixed

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A087a0