

View Online at <https://aerobasegroup.com/nsn/4140-00-417-8838>

Speed Adjustments:

Single speed

Width:

6.060 inches

Length:

5.562 inches

Flow Direction:

Outward

Environmental Protection:

Salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

40.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

1710.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 6 threaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

130.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.037 horsepower

Housing Inside Diameter:

5.940 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

400.0

Height:

7.000 inches

Material:

Plastic polysulfone blade

Quantity:

1

Surface Treatment:

Paint housing

Surface Treatment Specification:

Mil-e-5557 military specification single treatment response housing

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-e-5557 spec.