

View Online at <https://aerobasegroup.com/nsn/4140-00-417-8838>

**Speed Adjustments:**

Single speed

**Width:**

6.060 inches

**Length:**

5.562 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

40.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

1710.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange and 6 threaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

130.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.037 horsepower

**Housing Inside Diameter:**

5.940 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

400.0

**Height:**

7.000 inches

**Material:**

Plastic polysulfone blade

**Quantity:**

1

**Surface Treatment:**

Paint housing

**Surface Treatment Specification:**

Mil-e-5557 military specification single treatment response housing

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-e-5557 spec.