

View Online at <https://aerobasegroup.com/nsn/4140-00-432-0330>

**Speed Adjustments:**

Single speed

**Length:**

5.800 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Moisture resistant and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

0.0 degrees celsius and 90.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

11500.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange and 8 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

550.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac or 208.0 ac

**Prime Mover Power Rating:**

1.139 horsepower

**Housing Inside Diameter:**

4.320 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Aluminum alloy

**Surface Treatment:**

Enamel lusterless

**Style Designator:**

Fixed

**Test Data Document:**

13499-009-1900-010 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0