

View Online at <https://aerobasegroup.com/nsn/4140-00-433-6033>

**Stage Quantity:**

1

**Diameter:**

Between 21.345 inches and 21.350 inches

**Length:**

68.375 inches

**Operating Speed At Rated Capacity In Rpm:**

7480.0

**Static Pressure At Specificationified Air Flow Rate:**

40.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Steam turbine

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

12 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

21500.0 cubic feet per minute

**Prime Mover Power Rating:**

193.700 horsepower

**Housing Inside Diameter:**

30.000 inches

**Material:**

Steel housing

**Material Specification:**

Fed standard 66, aisi 403/sae 51403 federal standard single material response blade

**Quantity:**

1

**Style Designator:**

Fixed

**Reference Number Differentiating Characteristics:**

As differentiated by left hand air discharge configuration and shall be furnished without the following items, two /2/ each remotely mounted tachometers, fisher filter regulator, hagen relay sender, two /2/ bailey three-way transfer valves, hagen airlock valve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0