

View Online at <https://aerobasegroup.com/nsn/4140-00-433-6034>

Stage Quantity:

1

Diameter:

Between 21.345 inches and 21.350 inches

Length:

68.375 inches

Operating Speed At Rated Capacity In Rpm:

7480.0

Static Pressure At Specificationified Air Flow Rate:

40.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Steam turbine

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

12 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

21500.0 cubic feet per minute

Prime Mover Power Rating:

193.700 horsepower

Housing Inside Diameter:

30.000 inches

Material:

Steel housing

Material Specification:

Fed standard 66, aisi 403/sae 51403 federal standard single material response blade

Quantity:

1

Style Designator:

Fixed

Reference Number Differentiating Characteristics:

As differentiated by right hand air discharge configurationand shall be furnished without the following items, two /2/ each remotely mounted tachometers, fisher filter regulator, hagen relay sender, two /2/ bailey three-way transfer valves, hagenair lock valve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0