

View Online at <https://aerobasegroup.com/nsn/4140-00-434-4999>

Speed Adjustments:

Single speed

Length:

5.000 inches

Flow Direction:

Inward

Environmental Protection:

Humidity proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-20.0 degrees celsius and 75.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3900.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.5 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 6 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

150.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.105 horsepower

Housing Inside Diameter:

7.500 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Special Features:

Two .166 in. Diameter holes in mounting spider

Frequency In Hertz:

400.0

Material:

Steel housing

Surface Treatment:

Cadmium housing

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0