

View Online at <https://aerobasegroup.com/nsn/4140-00-442-3490>

Speed Adjustments:

Single speed

Length:

1.500 inches

Flow Direction:

Inward

Ambient Temperature At Full Rated Power:

-28.0 degrees celsius and 70.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

2700.0 and 3100.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 8 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

115.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

15.0 watts

Housing Inside Diameter:

4.517 inches

Prime Mover Drive Shaft Bearing Type:

Sleeve

Phase:

Single

Special Features:

4.688 in. Sq flange both ends venturi tube

Frequency In Hertz:

50.0 and 60.0

Material:

Plastic polycarbonate blade

Surface Treatment:

Zinc blade

Style Designator:

Fixed

Type/model Designation (non-core):

Mx2a3

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0