

View Online at <https://aerobasegroup.com/nsn/4140-00-442-3490>

**Speed Adjustments:**

Single speed

**Length:**

1.500 inches

**Flow Direction:**

Inward

**Ambient Temperature At Full Rated Power:**

-28.0 degrees celsius and 70.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

2700.0 and 3100.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange and 8 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

115.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

15.0 watts

**Housing Inside Diameter:**

4.517 inches

**Prime Mover Drive Shaft Bearing Type:**

Sleeve

**Phase:**

Single

**Special Features:**

4.688 in. Sq flange both ends venturi tube

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Plastic polycarbonate blade

**Surface Treatment:**

Zinc blade

**Style Designator:**

Fixed

**Type/model Designation (non-core):**

Mx2a3

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0