

View Online at <https://aerobasegroup.com/nsn/4140-00-471-5396>

Stage Quantity:

1

Speed Adjustments:

Single speed

Width:

19.000 inches

Length:

8.500 inches

Environmental Protection:

Moisture resistant

Ambient Temperature At Full Rated Power:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit

Operating Speed At Rated Capacity In Rpm:

3000.0

Electrical Connection Type:

Cord w/attached plug

Outlet Inside Width:

3.094 inches

Outlet Inside Height:

2.469 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 rack and 4 slot

Rotation Direction For Which Designed:

Clockwise or counterclockwise

Features Provided:

Air filter and louver

Air Flow Rate:

350.0 cubic feet per minute

Outlet Location:

Bottom

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.268 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Angular up

Phase:

Single

Height:

7.000 inches

Material:

Steel

Quantity:

2

Surface Treatment:

Enamel

Surface Treatment Specification:

Mil-e-15090b military specification single treatment response

Style Designator:

Fixed, dual, rectangular outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-e-15090b spec.