

View Online at <https://aerobasegroup.com/nsn/4140-00-474-9973>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Width:**

5.812 inches

**Length:**

5.141 inches

**Environmental Protection:**

Humidity proof and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 71.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3300.0

**Electrical Connection Type:**

Wire lead

**Outlet Inside Width:**

2.062 inches

**Outlet Inside Height:**

2.406 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 threaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

95.0 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.020 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Phase:**

Single

**Special Features:**

W/o mtg flange

**Frequency In Hertz:**

50.0 and 60.0

**Height:**

5.500 inches

**Material:**

Steel

**Quantity:**

1

**Surface Treatment:**

Cadmium blade and chromate blade

**Style Designator:**

Fixed, rectangular outlets

**Test Data Document:**

94117-110019+1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0