

View Online at <https://aerobasegroup.com/nsn/4140-00-474-9973>

Stage Quantity:

1

Speed Adjustments:

Single speed

Width:

5.812 inches

Length:

5.141 inches

Environmental Protection:

Humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 71.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3300.0

Electrical Connection Type:

Wire lead

Outlet Inside Width:

2.062 inches

Outlet Inside Height:

2.406 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 threaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

95.0 cubic feet per minute

Outlet Location:

Top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.020 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Horizontal

Phase:

Single

Special Features:

W/o mtg flange

Frequency In Hertz:

50.0 and 60.0

Height:

5.500 inches

Material:

Steel

Quantity:

1

Surface Treatment:

Cadmium blade and chromate blade

Style Designator:

Fixed, rectangular outlets

Test Data Document:

94117-110019+1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0