

View Online at <https://aerobasegroup.com/nsn/4140-00-480-1517>

Speed Adjustments:

Single speed

Diameter:

2.348 inches

Length:

2.250 inches

Flow Direction:

Outward

Environmental Protection:

Humidity proof and splash proof and vibration proof

Ambient Temperature At Full Rated Power:

-40.0 degrees celsius and 90.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

19000.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

2.1 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

68.0 cubic feet per minute

Voltage In Volts And Current Type:

128.0 ac

Prime Mover Power Rating:

0.087 horsepower

Housing Inside Diameter:

2.438 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

400.0

Material:

Aluminum blade

Quantity:

1

Surface Treatment:

Anodize blade

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0