

View Online at <https://aerobasegroup.com/nsn/4140-00-480-1517>

**Speed Adjustments:**

Single speed

**Diameter:**

2.348 inches

**Length:**

2.250 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Humidity proof and splash proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-40.0 degrees celsius and 90.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

19000.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

2.1 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 rim

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

68.0 cubic feet per minute

**Voltage In Volts And Current Type:**

128.0 ac

**Prime Mover Power Rating:**

0.087 horsepower

**Housing Inside Diameter:**

2.438 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

400.0

**Material:**

Aluminum blade

**Quantity:**

1

**Surface Treatment:**

Anodize blade

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0