Centrifugal Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-00-482-8364

| Speed Adjustme    | ents:  |
|-------------------|--|
| Single speed      |  |
| Width:            |  |
| 19.000 inches     |  |
| Length:           |  |
| 18.000 inches     |  |
| Environmental     | Protection:  |
| Corrosion resista | nt and fungus resistant and moisture resistant and shock proof and vibration proof |
| Ambient Tempu     | rature At Full Rated Power:  |
| -65.0 degrees fa  | nrenheit and 250.0 degrees fahrenheit  |
| Operating Spee    | d At Rated Capacity In Rpm:  |
| 3000.0            |  |
| Electrical Conn   | ection Type:   |
| Wire lead         |  |
| Static Pressure   | At Specificationified Air Flow Rate:   |
| 0.0 inches of wat | er   |
| Drive Type:       |  |
| Direct            |  |
| Prime Mover Ty    | pe:  |
| Electric motor    |  |
| Inclosure Type:   |  |
| Fully enclosed    |  |
| Rotation Directi  | on For Which Designed:   |
| Clockwise and co  | punterclockwise  |
| Air Flow Rate:    |  |
| 350.0 cubic feet  | per minute   |
| Voltage In Volts  | And Current Type:  |
| 115.0 ac          |  |
| Prime Mover Po    | wer Rating:  |
| 0.268 horsepowe   | er en  |
| Prime Mover Dr    | ive Shaft Bearing Type:  |
| Ball              |  |
| Discharge Direc   | tion:  |
| Angular up        |  |
| Phase:            |  |
| Single            |  |
| Frequency In He   | ertz:  |
| 50.0 and 60.0     |  |
| Height:           |  |
| 7.000 inches      |  |
| Material:         |  |
| Steel             |  |

## NSN 4140-00-482-8364

Centrifugal Fan - Page 2 of 2



Quantity:

2

Surface Treatment:

Enamel housing outside

Style Designator:

Fixed, dual, rectangular outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0