

View Online at <https://aerobasegroup.com/nsn/4140-00-482-9212>

**Speed Adjustments:**

Single speed

**Length:**

7.875 inches

**Flow Direction:**

Outward

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 70.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

5600.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange and 3 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Safety impeller guard

**Air Flow Rate:**

1650.0 cubic feet per minute

**Voltage In Volts And Current Type:**

208.0 ac

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-a-8625 spec.