

View Online at <https://aerobasegroup.com/nsn/4140-00-486-0396>

Stage Quantity:

1

Speed Adjustments:

Single speed

Length:

Between 1.458 inches and 1.478 inches

Flow Direction:

Outward

Environmental Protection:

Shock proof and vibration proof

Ambient Temperature At Full Rated Power:

125.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

19000.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 ring

Rotation Direction For Which Designed:

Counterclockwise

Features Provided:

Nonsparking

Air Flow Rate:

19.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.023 horsepower

Housing Inside Diameter:

Between 1.552 inches and 1.572 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

400.0

Material:

Aluminum alloy a380.0

Material Specification:

Qq-a-591 federal specification single material response

Surface Treatment:

Enamel

Surface Treatment Specification:

Mil-e-5557, type 4 military specification single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-e-5557 spec.