

View Online at <https://aerobasegroup.com/nsn/4140-00-490-0630>

**Speed Adjustments:**

Single speed

**Width:**

9.188 inches

**Diameter:**

5.000 inches

**Length:**

7.219 inches

**Environmental Protection:**

Humidity proof and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

70.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3650.0

**Electrical Connection Type:**

Wire lead

**Outlet Inside Width:**

3.688 inches

**Outlet Inside Height:**

1.578 inches

**Static Pressure At Specificationified Air Flow Rate:**

3.2 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

4 threaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

250.0 cubic feet per minute

**Outlet Location:**

Bottom

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.408 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Vertical down

**Phase:**

Single

**Special Features:**

Inlet rim w/clamp

**Height:**

7.781 inches

**Material:**

Steel

**Quantity:**

1

**Surface Treatment:**

Cadmium blade

**Style Designator:**

Fixed, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0