

View Online at <https://aerobasegroup.com/nsn/4140-00-493-9638>

**Speed Adjustments:**

Single speed

**Length:**

1.500 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Dustproof and fungus resistant and moisture resistant and salt spray resistant and shock proof and vibration proof

**Operating Speed At Rated Capacity In Rpm:**

3150.0

**End Application:**

6w/s: test consoles, mini-space; kidd class ddg; forrestal class cv; spruance class dd (963); los angeles class ssn (688); close in weapon system (ciws-phalanx); nimitz class cvn; aircraft, t-39; ticonderoga class cg (47); sturgeon class ssn (637)

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange and 8 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

46.000 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.037 horsepower

**Housing Inside Diameter:**

3.437 inches

**Phase:**

Single

**Special Features:**

3.625 in. Sq flange both ends venturi tube

**Frequency In Hertz:**

60.0

**Material:**

Zinc alloy housing

**Surface Treatment:**

Enamel housing outside

**Style Designator:**

Fixed

**Test Data Document:**

10236-7310006 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0