

View Online at <https://aerobasegroup.com/nsn/4140-00-493-9638>

Speed Adjustments:

Single speed

Length:

1.500 inches

Flow Direction:

Outward

Environmental Protection:

Dustproof and fungus resistant and moisture resistant and salt spray resistant and shock proof and vibration proof

Operating Speed At Rated Capacity In Rpm:

3150.0

End Application:

6w/s: test consoles, mini-space; kidd class ddg; forrestal class cv; spruance class dd (963); los angeles class ssn (688); close in weapon system (ciws-phalanx); nimitz class cvn; aircraft, t-39; ticonderoga class cg (47); sturgeon class ssn (637)

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 8 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

46.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.037 horsepower

Housing Inside Diameter:

3.437 inches

Phase:

Single

Special Features:

3.625 in. Sq flange both ends venturi tube

Frequency In Hertz:

60.0

Material:

Zinc alloy housing

Surface Treatment:

Enamel housing outside

Style Designator:

Fixed

Test Data Document:

10236-7310006 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0