NSN 4140-00-495-2848

Vaneaxial Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-00-495-2848

| Stage Quantity: |
|---|
| 1 |
| Speed Adjustments: |
| |
| Single speed |
| Length: 1.580 inches |
| Flow Direction: |
| Inward |
| |
| Operating Speed At Rated Capacity In Rpm: 20000.0 |
| |
| Electrical Connection Type: Terminal |
| Static Pressure At Specificationified Air Flow Rate: |
| 0.0 inches of water |
| |
| Drive Type: Direct |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Type And Quantity: |
| 3 unthreaded hole |
| Rotation Direction For Which Designed: |
| Counterclockwise |
| Air Flow Rate: |
| 58.0 cubic feet per minute |
| Voltage In Volts And Current Type: |
| 115.0 ac |
| Housing Inside Diameter: |
| 1.890 inches |
| Prime Mover Drive Shaft Bearing Type: |
| Ball |
| Phase: |
| Single |
| Frequency In Hertz: |
| 400.0 |
| Material: |
| Aluminum |
| Surface Treatment: |
| Enamel |
| Surface Treatment Specification: |
| Mil-e-5557, type 4 military specification single treatment response |
| |

NSN 4140-00-495-2848

Vaneaxial Fan - Page 2 of 2

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-e-5557 spec.

