

View Online at <https://aerobasegroup.com/nsn/4140-00-497-2134>

**Speed Adjustments:**

Single speed

**Diameter:**

3.075 inches

**Length:**

0.900 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Dustproof

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 95.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

13000.0

**Electrical Connection Type:**

Terminal

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Open

**Mounting Facility Type And Quantity:**

1 flange and 3 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

50.000 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.020 horsepower

**Housing Inside Diameter:**

3.120 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Quantity:**

1

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 1 military specification single treatment response

**Style Designator:**

Fixed

**Test Data Document:**

35351-147087-01 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-a-8625 spec.