

View Online at <https://aerobasegroup.com/nsn/4140-00-497-2134>

Speed Adjustments:

Single speed

Diameter:

3.075 inches

Length:

0.900 inches

Flow Direction:

Inward

Environmental Protection:

Dustproof

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 95.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

13000.0

Electrical Connection Type:

Terminal

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Mounting Facility Type And Quantity:

1 flange and 3 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

50.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.020 horsepower

Housing Inside Diameter:

3.120 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

400.0

Material:

Aluminum

Quantity:

1

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Fixed

Test Data Document:

35351-147087-01 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-a-8625 spec.