NSN 4140-00-497-2137

Centrifugal Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-00-497-2137

Single speed Width: 19.000 inches Length: Between 6.250 inches and 7.000 inches Operating Speed At Rated Capacity In Rpm: 3000.0 Electrical Connection Type: Cord w/attached plug Static Pressure At Specificationified Air Flow Rate: 0.0 inches of water Drive Type: Direct Prime Mover Type: Electric motor Features Provided: Safety impeller guard Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator: Fixed, dual, rectangular outlets	Speed Adjustments:	
19.000 inches Length: Between 6.250 inches and 7.000 inches Operating Speed At Rated Capacity In Rpm: 3000.0 Electrical Connection Type: Cord w/attached plug Static Pressure At Specificationified Air Flow Rate: 0.0 inches of water Drive Type: Direct Prime Mover Type: Electric motor Features Provided: Safety impeller guard Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Single speed	
Length: Between 6.250 inches and 7.000 inches Operating Speed At Rated Capacity In Rpm: 3000.0 Electrical Connection Type: Cord w/attached plug Static Pressure At Specificationified Air Flow Rate: 0.0 inches of water Drive Type: Direct Prime Mover Type: Electric motor Features Provided: Safety impeller guard Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Width:	
Detween 6.250 inches and 7.000 inches Operating Speed At Rated Capacity In Rpm: 3000.0 Electrical Connection Type: Cord w/attached plug Static Pressure At Specificationified Air Flow Rate: 0.0 inches of water Drive Type: Direct Prime Mover Type: Electric motor Features Provided: Safety impeller guard Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	19.000 inches	
Operating Speed At Rated Capacity In Rpm: 3000.0 Electrical Connection Type: Cord w/attached plug Static Pressure At Specificationified Air Flow Rate: 0.0 inches of water Drive Type: Direct Prime Mover Type: Electric motor Features Provided: Safety impeller guard Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Length:	
Blectrical Connection Type: Cord w/attached plug Static Pressure At Specificationified Air Flow Rate: 0.0 inches of water Drive Type: Direct Prime Mover Type: Electric motor Features Provided: Safety impeller guard Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Between 6.250 inches and 7.000 inches	
Electrical Connection Type: Cord w/attached plug Static Pressure At Specificationified Air Flow Rate: 0.0 inches of water Drive Type: Direct Prime Mover Type: Electric motor Features Provided: Safety impeller guard Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Operating Speed At Rated Capacity In Rpm:	
Static Pressure At Specificationified Air Flow Rate: 0.0 inches of water Drive Type: Direct Prime Mover Type: Electric motor Features Provided: Safety impeller guard Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	3000.0	
Static Pressure At Specificationified Air Flow Rate: 0.0 inches of water Drive Type: Direct Prime Mover Type: Electric motor Features Provided: Safety impeller guard Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Electrical Connection Type:	
O.0 inches of water Drive Type: Direct Prime Mover Type: Electric motor Features Provided: Safety impeller guard Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Cord w/attached plug	
Drive Type: Direct Prime Mover Type: Electric motor Features Provided: Safety impeller guard Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Static Pressure At Specificationified Air Flow Rate:	
Direct Prime Mover Type: Electric motor Features Provided: Safety impeller guard Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	0.0 inches of water	
Prime Mover Type: Electric motor Features Provided: Safety impeller guard Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Drive Type:	
Electric motor Features Provided: Safety impeller guard Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Direct	
Features Provided: Safety impeller guard Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Prime Mover Type:	
Safety impeller guard Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Electric motor	
Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Features Provided:	
300.0 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Safety impeller guard	
Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Air Flow Rate:	
Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	300.0 cubic feet per minute	
Voltage In Volts And Current Type: 115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Outlet Location:	
115.0 ac Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Bottom	
Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Voltage In Volts And Current Type:	
Ball Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	115.0 ac	
Discharge Direction: Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Prime Mover Drive Shaft Bearing Type:	
Angular up Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Ball	
Phase: Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Discharge Direction:	
Single Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Angular up	
Height: 5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Phase:	
5.250 inches Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Single	
Quantity: 2 Surface Treatment: Paint housing outside Style Designator:	Height:	
2 Surface Treatment: Paint housing outside Style Designator:	5.250 inches	
Surface Treatment: Paint housing outside Style Designator:	Quantity:	
Paint housing outside Style Designator:	2	
Style Designator:	Surface Treatment:	
	Paint housing outside	
Fixed, dual, rectangular outlets	Style Designator:	
. mou, addi, rotangula outlo	Fixed, dual, rectangular outlets	
Reference Number Differentiating Characteristics:	Reference Number Differentiating Characteristics:	
As differentiated by the voltagerequirement	As differentiated by the voltagerequirement	
As differentiated by the voltagerequirement	, , ,	
As differentiated by the voltagerequirement	, , ,	

N/a

NSN 4140-00-497-2137

Centrifugal Fan - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A087a0