

View Online at <https://aerobasegroup.com/nsn/4140-00-499-5731>

Speed Adjustments:

Single speed

Length:

7.880 inches

Flow Direction:

Outward

Environmental Protection:

Fungus resistant and humidity proof and salt spray resistant and shock proof and vibration proof

Operating Speed At Rated Capacity In Rpm:

3700.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 8 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

1150.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.395 horsepower

Housing Inside Diameter:

9.120 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Material:

Aluminum

Surface Treatment:

Anodize

Style Designator:

Fixed

Test Data Document:

97942-128c890h01 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0