

View Online at <https://aerobasegroup.com/nsn/4140-00-505-1664>

Speed Adjustments:

Single speed

Length:

2.281 inches

Flow Direction:

Inward

Environmental Protection:

Humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-54.0 degrees celsius and 85.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

11250.0

Electrical Connection Type:

Terminal box

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 clamp ring

Rotation Direction For Which Designed:

Counterclockwise

Features Provided:

Safety impeller guard

Air Flow Rate:

200.0 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

0.092 horsepower

Housing Inside Diameter:

3.500 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Material:

Aluminum

Quantity:

1

Surface Treatment:

Enamel

Surface Treatment Specification:

Mil-e-5557, type 4 military specification single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0

Mil-std (military Standard):

Mil-e-5557 spec.