

View Online at <https://aerobasegroup.com/nsn/4140-00-510-3699>

Stage Quantity:

1

Speed Adjustments:

Single speed

Length:

1.580 inches

Flow Direction:

Outward

Environmental Protection:

Explosion proof

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 125.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3000.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 clamp ring

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

7.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.015 horsepower

Housing Inside Diameter:

1.890 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

50.0 and 60.0

Material:

Aluminum

Surface Treatment:

Enamel

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0