

View Online at <https://aerobasegroup.com/nsn/4140-00-516-5002>

Speed Adjustments:

Single speed

Length:

38.875 inches

Flow Direction:

Inward

Operating Speed At Rated Capacity In Rpm:

1750.0

End Application:

W/s: wasp class lhd; tarawa class lha; supply class aoe; an/srn-2 (v) navigation radio set; cvn 68 class reactor fill auxiliary system; nimitz class cvn; fms-newport class lst; forrestal class cv; fms-knox class ff; whidbey island class lsd

Electrical Connection Type:

Terminal box

Static Pressure At Specificationified Air Flow Rate:

4.5 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Mounting Facility Type And Quantity:

1 flange

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

20000.0 cubic feet per minute

Voltage In Volts And Current Type:

440.0 ac

Prime Mover Power Rating:

17.500 horsepower

Housing Inside Diameter:

36.000 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

60.0

Material:

Steel housing

Surface Treatment:

Zinc housing outside

Style Designator:

Fixed

Specification Or Standard:

A type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-f-18953 spec.