

View Online at <https://aerobasegroup.com/nsn/4140-00-518-2719>

Stage Quantity:

1

Speed Adjustments:

Single speed

Width:

6.938 inches

Diameter:

1.500 inches

Length:

2.641 inches

Environmental Protection:

Humidity proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-20.0 degrees celsius and 75.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

7800.0

Electrical Connection Type:

Terminal block

Outlet Inside Width:

1.312 inches

Outlet Inside Height:

1.250 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Safety impeller guard

Air Flow Rate:

46.000 cubic feet per minute

Outlet Location:

Top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.032 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Horizontal

Phase:

Three

Height:

3.937 inches

Material:

Steel blade

Quantity:

2

Style Designator:

Fixed, dual impeller, rectangular outlet

Test Data Document:

10001-2994915-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0