

View Online at <https://aerobasegroup.com/nsn/4140-00-518-2719>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Width:**

6.938 inches

**Diameter:**

1.500 inches

**Length:**

2.641 inches

**Environmental Protection:**

Humidity proof and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-20.0 degrees celsius and 75.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

7800.0

**Electrical Connection Type:**

Terminal block

**Outlet Inside Width:**

1.312 inches

**Outlet Inside Height:**

1.250 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Safety impeller guard

**Air Flow Rate:**

46.000 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.032 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Phase:**

Three

**Height:**

3.937 inches

**Material:**

Steel blade

**Quantity:**

2

**Style Designator:**

Fixed, dual impeller, rectangular outlet

**Test Data Document:**

10001-2994915-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0