

View Online at <https://aerobasegroup.com/nsn/4140-00-518-2744>

Speed Adjustments:

Single speed

Length:

1.625 inches

Flow Direction:

Inward

Environmental Protection:

Shock proof and salt spray resistant

Ambient Temperature At Full Rated Power:

125.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3300.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

110.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.017 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

50.0 and 60.0

Material:

Plastic polycarbonate blade

Surface Treatment:

Enamel housing

Surface Treatment Specification:

Mil-e-5557, type 4 military specification single treatment response housing

Style Designator:

Fixed

Test Data Document:

56232-560975 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-e-5557 spec.