

View Online at <https://aerobasegroup.com/nsn/4140-00-518-2744>

**Speed Adjustments:**

Single speed

**Length:**

1.625 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Shock proof and salt spray resistant

**Ambient Temperature At Full Rated Power:**

125.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3300.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

110.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.017 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Plastic polycarbonate blade

**Surface Treatment:**

Enamel housing

**Surface Treatment Specification:**

Mil-e-5557, type 4 military specification single treatment response housing

**Style Designator:**

Fixed

**Test Data Document:**

56232-560975 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-e-5557 spec.