

View Online at <https://aerobasegroup.com/nsn/4140-00-522-2941>

Stage Quantity:

1

Speed Adjustments:

Single speed

Width:

8.578 inches

Diameter:

3.000 inches

Length:

6.310 inches

Environmental Protection:

Moisture resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-54.0 degrees celsius and 55.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

5500.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

8 threaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

214.0 cubic feet per minute

Outlet Location:

Bottom or top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.174 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Angular down and angular up and horizontal and vertical down and vertical up

Phase:

Single

Height:

5.810 inches

Material:

Steel

Surface Treatment:

Zinc blade

Style Designator:

Fixed, dual impeller, round outlet

Test Data Document:

13499-009-1920-010 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0