

View Online at <https://aerobasegroup.com/nsn/4140-00-529-0844>

Stage Quantity:

1

Speed Adjustments:

Single speed

Diameter:

11.750 inches

Length:

16.000 inches

Flow Direction:

Inward

Environmental Protection:

Splash proof

Ambient Temperature At Full Rated Power:

50.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

1750.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

2.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

1000.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.500 horsepower

Housing Inside Diameter:

14.438 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

60.0

Material:

Steel housing

Quantity:

1

Surface Treatment:

Zinc housing outside

Style Designator:

Fixed

Test Data Document:

81349-milf18953 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Reference Number Differentiating Characteristics:

As differentiated by peerless electric co motor dwg no. D-2722

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0